

## DCNET X7C ENTERPRISE IP PHONE



### Introduction

With a modern, clear design, X7C is a high-end enterprise IP phone for business users who need immediate access to all of their important information. In addition to a 5-inch high-resolution color screen, the telephone also features 20 SIP lines, HD audio with Opus support, up to 60 DSS keys (12 physical), Built-in Bluetooth, Wi-Fi connectivity and more!

### Highlights

- Make in India
- TEC Approved
- Indian MAC ID
- 20 SIP lines
- HD audio on speakerphone and handset.

- 5" high-resolution color display
- Built-in Bluetooth for connecting Bluetooth headset
- Wi-Fi connectivity (Via Wi-Fi dongle)
- Up to 60 DS Video Codec H.264 s
- Dual Gigabit ports, integrated PoE
- Stand with 2 adjustable angles of 40 and 50 degrees

## Generic

- 20 SIP Lines
- HD Voice
- Support receiving Video call
- PoE Enabled
- 5 Inch Color LCD Screen
- Handset / Hands-free / Headset mode
- Intelligent DSS Keys
- Optional External Power Supply

## Phone Function

- Local Phonebook (2000 entries)
- Remote Phonebook (XML/LDAP, 2000 entries)
- Call logs (In/out/missed, 1000 entries)
- Blocked /Allowed List
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Built-in Bluetooth 4.2: Support Bluetooth headset
- Support Wi-Fi Dongle
- Support Plantronics wireless headset (Through Plantronics APD-80 EHS Cable)
- Support Jabra wireless headset (Through Fanvil EHS20 EHS Cable)
- Support Recording (Through Flash Drive or Server Recording)
- Action URL / Active URI
- uaCSTA

## Call Function

- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice message (with server)
- 6-way audio conference
- Hot line
- Hot desking

## Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
- HAC handset
- Wideband ADC/DAC 16KHz Sampling
- Narrowband Codec: G.711a/u, G.723.1, G.726-32K, G.729AB, G.726-16, G.726-24, G.726-40, iLBC
- Wideband Codec: G.722, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR) / Automatic Gain Control (AGC)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band – DTMF-Relay(RFC2833) / SIP INFO

## Network

- Physical: 10/100/1000 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode:IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- QoS
- RTCP-XR(RFC3611), VQ-RTCPXR(RFC6035)
- Wi-Fi Security Mode: WPA /WPA2-PSK/802.X EAP

## Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- IPv6
- LLDP
- PPPoE
- 802.1x
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069
- AES128 & AES256

## Deployment & Management

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP  
OPT66/SIP PNP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog

- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT5 Ethernet Cable x1
- Back Rack x1
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- USB2.0 Port x1: Standard A, Connect with  
Wi-Fi USB dongle or Flash Driver
- DC Power Input: 5V/2A
- Power Consumption (PoE): 2.6~ 9W
- Power Consumption (Adapter): 2.4~8W
- Working Temperature: 0~45°C
- Working Humidity: 10~95%
- Qty/CTN: 10pcs
- N.W/CTN: 16.6kg
- G.W/CTN: 17.72kg
- Installation: Desktop Stand
- Color: Black
- Device Dimensions
  - Desktop Stand (Angles 1): 268 x 185 x 189mm
  - Desktop Stand (Angles 2): 268 x 201 x 168mm
- Gift Box Dimensions: 304 x 297 x 66mm
- Outer CTN Dimensions: 616 x 358 x 329mm (10 PCS)

## Physical Specifications

- Main LCD x1: 5.0 inch (800x480) Color screen
- Keypad: 43 keys, including
  - 4 Soft-keys
  - 12 DSS Keys with tri-color LED
  - 1 Page-Switch (PS) key
  - 5 Function keys (Hold, MWI,Mute,Headset, Redial)
  - 4 Navigation keys
  - 1 OK key
  - 1 Return key
  - 12 Standard Phone Digits keys
  - 2 Volume Control keys, Up/Down
  - 1 Hands-free key

\*Our product comply Local Content requirements prescribed in Ministry of Commerce and Industry Department for Promotion of Industry and Internal Trade Order No. P-45021/2/2017-PP (BE-II) Dated 04-June-2020 under Class-I/Class-II Local Supplier with more than 20%/50% Local Content with value addition.



**Registered Office:** 2704/8, "shivalay", 7th Main, Next To Dr.Mothi's Clinic, Yadav giri, Mysore, Karnataka 570020

**Corporate Office:** 3rd Floor, No 28, DCNET BUILDING, 5th Cross, 6th Main Rd, Mico Layout, BTM 2nd Stage, Bengaluru, Karnataka 560076

**Mumbai Branch Office:** Shop No.6,Ground Floor Shri Sai Samarth Chs Building, Jivadaya Lan, Ghatkopar West, Mumbai 400086

**Delhi Branch Office:** B-38/39, Mohan Garden, D.K. Road, Pillar No.751, New Delhi 110059

**Noida Branch Office:** E-57, Ground Floor, Sector-3, Noida, UP 201301

**Contact:** +91 9880067000, +91 9945160901

**Email:** info@dcnetindia.com

**Website:** www.dcnetindia.com